


Comparison of Low-Loss Melt-Draw Tapered Type and Which is More Reliable



Overview

For direct injections, the placement of the drilled hole is the only decision you need to make, with most applications finding the hole drilled at the top of the liner to be effective. For gaseous samples, an inlet liner with a narrow inner diameter is recommended to ensure a tight sample. Vectra liquid crystal polymers are a family of high-performance plastics based on patented Celanese technology. They guide material selection, quality control, and process optimization for injection molding, extrusion, and blow molding. This guide explains MFR/MFI, testing methods, and practical tips to. Abstract: Well established routes for obtaining strong polyethylene (PE) involve solid state drawing either of solution crystallized or melt crystallized spherulitic PE. The aim of this work is to show the potential of melt deformation as an alternative route for obtaining highly. However, with so many options to choose from, how do you determine which one is best for your analysis?

Generally, this question can be simplified based on your injection technique.



Article Content

Melt flow ratio: A way to identify the type of polyethylene

The purpose of this paper is, thus, to provide a fairly simple way to identify the type of PE by melt flow ratio (MFR) only using the melt indexer, a common quality control apparatus.

Understanding Melt Flow Rate & Index: A Guide to Optimizing ...

Getting reliable melt flow results is not only about using the right machine but also about how you use it. Small mistakes in testing can lead to big problems in production, so it's worth taking ...

Vectra_LCPdesignGuideBro_AM_1112_VC-7R3_72

Generally speaking, materials with high modulus, such as metals, have low damping (internal loss) characteristics and low modulus materials, such as rubbers, have high damping characteristics.

Melt strength and drawability of HDPE, LDPE and HDPE/LDPE blends

Because the branched type of molecular chain structure needs more stress to produce disentanglement than that of the linear type of molecular chain structure, the sensitivity of the melts ...

APPLIED ENGINEERING PRINCIPLES MANUAL

Throughout this manual, a lower case letter such as e or v for voltage, or i for current, signifies that the quantity varies with time. When discussing values which remain constant, capital letters...

Melt drawing as a route to high performance polyethylene

Here, we show that PE films (or filaments) can all be "melt drawn" in the temperature window 130-160 ~ thus yielding oriented products. The advantage of melt drawing over direct melt extrusion is that ...

M Entry Flow of Polyethylene Melts in Tapered Dies

Further simulations with a viscous (Cross) model have shown that they severely under-predict the entrance pressure by an order of magnitude for the more elastic melts.

Melt strength and drawability of HDPE, LDPE and HDPE/LDPE blends

A comparison among hybrid fillers/polypropylene compounds with and without MuCell® technology was investigated.

How to Choose a GC Inlet Liner

GC inlet liners are available in a multitude of styles. They differ in geometric design, volume and inner diameter, deactivation, and the presence or absence of some type of packing. ...

Manufacturing Materials Comparison Guide

Explore different plastic, metal, elastomer, and LSR materials to find the right manufacturing service and material for your prototypes or low-volume production parts.

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.budowasilesia.pl>

Email: contact@budowasilesia.pl

Phone: +48 537 192 846

Address: ul. Chorzowska 45, 40-001 Katowice, Silesian Voivodeship, Poland

This document is for informational purposes only. Specifications subject to change without notice.

